

Product Description

PPC complete systems are assembled in different versions, according to customer wishes. All complete systems are supplied in a sturdy aluminum case with individually designed pockets/sections and have space for the components listed below.

Included:

- 1 PPC-06-plus, PPC-08-plus or PPC-12 hydraulic tester
- 1 Power supply unit
- Up to 3 Pressure transmitter(s) with installed adaptor for STAUFF Test 20 (M 16 x 2)
- Up to 3 Connecting cable(s) (3 m / 10 ft.)
- 1 TS temperature sensor, with installed SGV-16S-G (optional)
- 3 SAD adaptors for the STAUFF Test 15/12/10 series (standard for all PPC complete systems)
- 1 Printed operating instructions (German or English)
- 1 Operating instructions (multilingual) on CD
- 1 PC software for the PPC-06/08-plus older PPC-12
- 1 PC connecting cable



DIAGTRONICS

Ordering System

PPC - 06 - SET - 3 T - * / *** / *****

Type	
PPC	Hydraulic Tester

Tester Version	
06-SET	3 sensor inputs, including PC software and PC connecting cable
08-SET	4 sensor inputs, including PC software and PC connecting cable
12-SET	6 sensor inputs, including PC software and PC connecting cable

Number of Pressure Transmitters	
1	with one pressure transmitter
2	with two pressure transmitters
3	with three pressure transmitters

Pressure Range Pressure Transmitter	
000/015/060/150/400/600/601	Pressure range Third pressure transmitter
000/015/060/150/400/600/601	Pressure range Second pressure transmitter
When ordering a complete system with one or two pressure transmitters, specify "000" for the pressure range of the second or third transmitters	
000/015/060/150/400/600/601	Pressure range First pressure transmitter
Please keep in mind that two pressure transmitters with identical measuring ranges are necessary for differential pressure measurements.	

Temperature Sensor	
Omit	without TS temperature sensor with SGV
T	with TS temperature sensor with SGV