

RTF48 N 25 ... B / S2 / V / X

Filter Type RTF47 RTF48 RTF49

Connection Style		Group	
Code	Connection style	Port A	Port B
B	BSP	G1-1/4 & 1-1/2 SAE flange	None
BB	BSP	G1-1/4 & 1-1/2 SAE flange	G1-1/4
N	NPT	1-1/4 NPT & 1-1/2 SAE flange	None
NN	NPT	1-1/4 NPT & 1-1/2 SAE flange	1-1/4 NPT
M	NPT	1-1/2 NPT	None
MN	NPT	1-1/2 NPT	1-1/4 NPT
MM	NPT	1-1/2 NPT	1-1/2 NPT
S	SAE	1-5/8 -12 UN	None
SS	SAE	1-5/8 -12 UN	1-5/8 -12 UN
ST	SAE	1-5/8 -12 UN	1-7/8 -12 UN
SU	SAE	1-5/8 -12 UN	2-1/2 -12 UN
SO	Combination	1-5/8 -12 UN	2 NPT

Design Code
only for information

Clogging Indicator

N	None
V	Visual
E	Electrical

See page F67 for more details on the indicator options.

Length

S1	for bowl length 1 (1 element)
S2	for bowl length 2 (2 elements)

Note: RTF 47 available in S1 bowl only

Seal Material

B	NBR (Buna-N®)
----------	---------------

other seal material on request

For Complete Filters:
identification filter material
+ micron rating code
(see ordering code filter elements below)

By-pass Valve

Code	By-pass setting
00	No by-pass
15	1 bar (15 PSI)
25	1.7 bar (25 PSI)

RTE48 D 10 B / X

Group
according to filter housing

Filter Material		Micron ratings available
Code	Material	
D	Filter paper	03, 10, 20, 25
G	Inorganic glass fiber	03, 10, 25

Design Code
only for information

Seal Material

B	NBR (Buna-N®)
----------	---------------

other seal material on request

Micron Rating

Code	Rating
03	03 µm
10	10 µm
20	20 µm
25	25 µm