

## Replacement Filter Elements for SF Series

STAUFF replacement filter elements for SF series filters are manufactured in the common filter materials such as stainless fiber, stainless mesh, cellulose and inorganic glass fiber. As standard, all replacement elements series SF, have tin plated steel parts for use with aggressive media such as water glycol, other materials available on request. All STAUFF replacement elements comply with quality specifications in accordance with international standards.



**SE 014 G 10 V /X**

**Series** SE

**Group**  
according to filter housing

Filter Material			Micron ratings available
Code	Material	max $\Delta p^*$ _{collapse}	
<b>A</b>	Stainless fiber	210 bar (3045 PSI)	03, 05, 10, 20
<b>G</b>	Inorganic glass fiber	30 bar (435 PSI)	
<b>H</b>	Inorganic glass fiber	210 bar (3045 PSI)	
<b>B, S</b>	Stainless mesh	30 bar (435 PSI)	25, 50, 100, 200

\*collapse / burst resistance as per ISO 2941

Bold type identifies preferred material, other materials or micron ratings on request

**Design Code**  
only for information

Seal Material	
<b>B</b>	NBR (Buna®)
<b>V</b>	FPM (Viton®)
<b>E</b>	EPDM
other seal materials on request	

Micron Rating	
<b>03</b>	3 $\mu$ m
<b>05</b>	5 $\mu$ m
<b>10</b>	10 $\mu$ m
<b>20</b>	20 $\mu$ m
<b>25</b>	25 $\mu$ m
<b>50</b>	50 $\mu$ m
<b>100</b>	100 $\mu$ m
<b>200</b>	200 $\mu$ m
other micron ratings on request	