

Replacement Filter Elements for SF/SFA Series

STAUFF replacement filter elements for SF/SFA series filters are manufactured in the common filter materials such as stainless fiber, stainless mesh, cellulose and inorganic glass fiber. As standard, all replacement elements series SF/SFA, have tin plated steel parts for use with aggressive media such as water glycol, other materials available on request. All STAUFF replacement elements comply with quality specifications in accordance with international standards.



SE 014 G 10 V /X

Series SE

Group
according to filter housing

Filter Material			Micron ratings available
Code	Material	max Δp^* collapse	
A	Stainless fiber	210 bar (3045 PSI)	03, 05, 10, 20
G	Inorganic glass fiber	30 bar (435 PSI)	
H	Inorganic glass fiber	210 bar (3045 PSI)	
B, S	Stainless mesh	30 bar (435 PSI)	25, 50, 100, 200

*collapse / burst resistance as per ISO 2941

Bold type identifies preferred material, other materials or micron ratings on request

Design Code
only for information

Seal Material	
B	NBR (Buna®)
V	FPM (Viton®)
E	EPDM
other seal materials on request	

Micron Rating	
03	3 μ m
05	5 μ m
10	10 μ m
20	20 μ m
25	25 μ m
50	50 μ m
100	100 μ m
200	200 μ m
other micron ratings on request	