

Ordering Code Filter Housings

SMPF 015 ... B - T B / B / E / X

Filter Type SMPF

Group

Size	Flow*	
	l/min	GPM
15	60	15
25	90	25

* Note: exact flow will depend on filter element selected. Consult technical data on page F25.

For Complete Filters:
identification filter material + micron rating code (see ordering code filter elements below)

Seal Material
B NBR (Buna®)
Other seal material on request

Design Code
only for information

Clogging Indicators

V	visual
E	visual / electrical

Valve

O	Without Valve
B	By-pass Valve

Connection Style

B	BSP	G ¹ / ₂
U	SAE O-Ring thread	³ / ₄ -16 UN

Mounting Style

T	In-line
---	---------

Ordering Code Filter Elements

SME 015 E 03 B / X

Series SME

Group
according to filter housing

Filter Material

Code	Material	max Δp* _{collapse}	Micron ratings available
E	Inorganic glass fiber	30 bar (435 PSI)	03,10,20
S	Stainless mesh	20 bar (290 PSI)	60

*collapse/ burst resistance as per ISO 2941

Design Code
only for information

Seal Material
B NBR (Buna®)
Other seal material on request

Micron Rating

Code	Rating
03	3 μm
10	10 μm
20	25 μm
60	60 μm

Other micron ratings on request

FILTRATION