

## Technical Data

The Stauff Portable Filter Cart (SPFC) is a very complete and practical unit capable of off-line filtration, filling or emptying reservoirs (if needed via 125µm suction filter) or any application requiring the transfer or filtration of hydraulic oils. Multi stage filtration can be applied to extend element lifetime. The SPFC is available with a variety of Spin-on elements for quick and easy element replacement as well with various pump/motor options. All components are mounted together on a sturdy frame guaranteeing a long lifetime.



Note: For special applications (fluids, temperature, etc.) please contact your local Stauff distributor.

## Technical Specification

- 38 l/min (10 US GPM) Gear Pump
- Electric Motor single phase or three phase 3/4 HP
- On/Off Button with 3m (10ft) Power cord
- Heavy Duty Welded Frame with Drip Pan and Tool Tray
- Suction Strainer - 100 Mesh Spin on
- 3m (10ft) Spiral Reinforced PVC Hoses with Wands
- 3-Way Ball Valve to By-pass Filters
- Weight: 86 Kg (190 lbs.)

## Options

- Single or Dual Stage Filtration
- 3, 6, 12 or 25µm βx= 200 Elements
- Water Absorption Elements
- Drum Cart
- Smart Cart with Laser Particle Monitor contamination indicator