

Test Hose SMS

	Length L		Order No.	Notice
	mm	in		
	305	12	SMS-10-305-B	Nominal bore 0.08" (2 mm) Minimum bending radius 0.75" (20 mm) Pressure/t° factor to 0°C 122 % at 30°C 110 % at 50°C 100 % at 80°C 86 % at 100°C 77 %
	610	24	SMS-10-610-B	
	915	36	SMS-10-915-B	
	1219	48	SMS-10-1219-B	
	1524	60	SMS-10-1524-B	
	1829	72	SMS-10-1829-B	
	2438	96	SMS-10-2438-B	
	3048	120	SMS-10-3048-B	
Hose length is in millimeters				

Test Hose SMS for direct gauge adaptor

	Length L		Order No.	Notice
	mm	in		
	305	12	SMS-10/N ¹ / ₄ -305mm-B	Nominal bore 0.08" (2 mm) Minimum bending radius 0.75" 20 mm Pressure/t° factor to 0°C 122 % at 30°C 110 % at 50°C 100 % at 80°C 86 % at 100°C 77 %
	610	24	SMS-10/N ¹ / ₄ -610mm-B	
	915	36	SMS-10/N ¹ / ₄ -915mm-B	
	1219	48	SMS-10/N ¹ / ₄ -1219mm-B	
	1524	60	SMS-10/N ¹ / ₄ -1524mm-B	
	1829	72	SMS-10/N ¹ / ₄ -1829mm-B	
	2438	96	SMS-10/N ¹ / ₄ -2438mm-B	
	3048	120	SMS-10/N ¹ / ₄ -3048mm-B	
Bending protection and other lengths on request.				

Gauge Adaptor SMA

	G	H		SW		Order No.	
		mm	in	mm	in	NBR (BUNA)	FPM (VITON) (Standard)
	G ¹ / ₄	57	2.24	19	0.75	SMA 10 - G ¹ / ₄ - P-OR	SMA 10 - G ¹ / ₄ - V-OR
	G ¹ / ₂	67	2.64	27	1.06	SMA 10 - G ¹ / ₂ - P-OR	SMA 10 - G ¹ / ₂ - V-OR
	¹ / ₄ NPT	57	2.24	19	0.75	SMA 10 - ¹ / ₄ NPT-P	SMA 10 - ¹ / ₄ NPT-V
	¹ / ₂ NPT	67	2.64	27	1.06	SMA 10 - ¹ / ₂ NPT-P	SMA 10 - ¹ / ₂ NPT-V
Damping element on request							