

Add on feature to lock or tag out valves used in pressure line in accordance with OSHA regulations.

Factory installed Locking Kit

Specifications

- Available for STAUFF valves up to 2" size.
Design changes for Direct Mount SAE Valve. Pad Lock not included. Plate is stainless steel, for block body and forged body two-way valves.



Locking Kit Part #	Fits	Valve Size
LD-BBV04-08	BBV/BBVM/CBV	1/8"-1/2" with SW9 Stem
LD-BBV12-24	BBV/BBVM/CBV	3/4"-1" & 1 1/4"-1 1/2" Reduced Bore
LD-FBV20-32	FBV	1 1/4"-2"

Field Installed Locking Kit

Specifications

- New design for easy field installation. No welding or drilling required. This tamper resistant design is available up to 2" size. Made of Zinc plated yellow chromated carbon steel. Pad lock not included.

- Accepts Standard Lock

Order Example

- Match stem dimension "SW" of Valve, with **bold SW** for kit number - add to valve

Kit #
LD **SW9** FI
LD **SW14** FI
LD **SW17** FI

i. e., BBV20160001M/LD **SW14** FI



**ALL VALVES ARE AVAILABLE WITH LOCKING DEVICE
CONTACT FACTORY FOR DETAILS ON VALVES NOT LISTED.**